



## RULE BREAKER

Create a textural look that will last with Rule Breaker. From the extensive range of warm, rich colors to the durability, Rule Breaker is made for commercial environments.



## RULE BREAKER

## RULE BREAKER 20

## RULE BREAKER 26

## RULE BREAKER 26 UNITARY

Style Number	2B94	2B92 (12') / 2B105 (15')	2B93 (12') / 2B106 (15')	2B103
Product Type	Broadloom	Broadloom	Broadloom	Broadloom
Construction	Tufted	Tufted	Tufted	Tufted
Surface Appearance	Level Loop	Level Loop	Level Loop	Level Loop
Gauge	1/10" (39.37 rows per 10 cm)	1/10" (39.37 rows per 10 cm)	1/10" (39.37 rows per 10 cm)	1/10" (39.37 rows per 10 cm)
Density	4,716	5,592	5,305	5,305
Dye Method	100% Solution Dyed	100% Solution Dyed	100% Solution Dyed	100% Solution Dyed
Fiber Type	EnviroStrand™ SD PET	EnviroStrand™ SD PET	EnviroStrand™ SD PET	EnviroStrand™ SD PET
Stain Release Technology	Mohawk Protection Plus Stain	Mohawk Protection Plus Stain	Mohawk Protection Plus Stain	Mohawk Protection Plus Stain
Soil Release Technology	Mohawk Protection Plus Soil	Mohawk Protection Plus Soil	Mohawk Protection Plus Soil	Mohawk Protection Plus Soil
Primary Backing	Woven Polypropylene	Woven Polypropylene	Woven Polypropylene	Woven Polypropylene
Secondary Backing	Weldlok®	Weldlok®	Weldlok®	Weldlok® Unitary
Indoor Air Quality	Green Label Plus Certified # 0350	Green Label Plus Certified # 0350	Green Label Plus Certified # 0350	Green Label Plus Certified # 0350
Size	12' width (3.66 m)	12' width (3.66 m), 15' width (4.57 m)	12' width (3.66 m), 15' width (4.57 m)	12' width (3.66 m)
Flammability	ASTM E648 Class 1 (Glue down)	ASTM E648 Class 1 (Glue down)	ASTM E648 Class 1 (Glue down)	ASTM E648 Class 1 (Glue down)
Smoke Density	ASTM 662 Less than 450	ASTM 662 Less than 450	ASTM 662 Less than 450	ASTM 662 Less than 450
Static Propensity	ATTCC-134 Under 3.5 KV	ATTCC-134 Under 3.5 KV	ATTCC-134 Under 3.5 KV	ATTCC-134 Under 3.5 KV
Warranties	10 Year Limited Wear 10 Year Limited Static Protection 10 Year Limited Stain Resistance 10 Year Limited Colorfastness to Light 10 Year Limited Colorfastness to Atmospheric Contaminants	10 Year Limited Wear 10 Year Static Protection 10 Year Limited Stain Resistance 10 Year Limited Colorfastness to Light 10 Year Limited Colorfastness to Atmospheric Contaminants	10 Year Limited Wear 10 Year Limited Static Protection 10 Year Limited Stain Resistance 10 Year Limited Colorfastness to Light 10 Year Limited Colorfastness to Atmospheric Contaminants	10 Year Limited Wear 10 Year Limited Static Protection 10 Year Limited Stain Resistance 10 Year Limited Colorfastness to Light 10 Year Limited Colorfastness to Atmospheric Contaminants

Cover: 979 Charcoal



383  
Clay



589  
Cobalt



748  
Praline



852  
Chestnut



869  
Hickory



889  
Walnut



949  
Pewter



959  
Nickel



979  
Charcoal



999  
Onyx

**EnviroStrand<sup>SD</sup>**